

OUR CUSTOMERS ARE OUR BEST  
REFERENCE



Inoxtruck

Garagaltza auzoa, 51- P.O. Box. 19  
20560 OÑATI (Gipuzkoa) SPAIN  
Norte 43° 2, 2233' W 2° 25, 1961'  
Tel: 902 702 919  
Fax: 943 780 917  
info@ulmainoxtruck.com  
www.ulmainoxtruck.com

## ELECTROMANUAL TILTERS RANGE



Inoxtruck

# EBT300



The ULMA Inoxtruck tilters, specially designed for the industry of seafood, meat, vegetables and dairy products are mobile models developed for effective turning /casting of containers, eurobins and drums to conveyor belts or working tables.

The turning system of ULMA Inoxtruck electromanual tilters offers to the operator an ergonomic handling and casting, avoiding unnecessary effort and possible personal injury.



The hygienic design makes them the ideal equipment for harsh environments, reducing the microbiological pollution and allowing a total daily cleaning, which is necessary on production centers with high hygiene demands.

## EBT300

Drums Tilter

## EBT300E

Eurobin DIN 9797 Tilter

# ELECTROMANUAL TILTERS RANGE

# EBT10



## EBT10S

Tilter with design of width/straddle forks.

## EBT10

Tilter with fixed height adapted to each need.



## EBT10i

Tilter with initial fork lift for different tilting heights.



- Manufactured in 100% Stainless Steel AISI 304L or 316L.
- IP65 Protection.
- Fully hygienic design for daily cleaning.
- Mobile, without need of civil works.
- Sealed bearings, free of lubrication.
- Moving wheels of Nylon with brakes.
- Hydraulic lifting System (Gel Battery).
- Casting Capacity: up to 100.000 kg per battery charge.
- Ergonomic and Tailor made design.



Range of Tilters	EBT300		EBT10			
	EBT300	EBT300E	EBT10S	EBT10	EBT10i	
Description	Drums Tilter	Eurobin Tilter	Width/ Straddle Forks	Standard	Initial	
Load Capacity	kg	300	300	1000	1000	
Tilting Angle	°	130	130	115	115	
Unloading Height	mm	1000-1600	1000-1600	900-1200	900-1400	
Push bar height	mm	1020	1020	940	940	
Tilting cycles max load		110	110	100	100	
Container	Width	mm	240-600	720	800-1000	800-1000
	Lenght	mm	240-600	730	1200	1200
	Height	mm	500-1200	700-950	600-1000	600-1000

• Todos los volteadores EBT10 están equipados con doble rodillo de carga en nylon.